

TECHNICAL SHEET SAMOA

Updated 26-12-2012

CHARACTERISTICS	VALUE		UNITS	STANDARDS
	WARP	WEFT		

OVERALL CHARACTERISTICS

Composition	80 % PAN - 20% IPES Permanent Fr			
Finish	Dyed piece			
Weave	Blackout			ISO 7211- 1
Weight	320		g/m ²	ISO 3801
Width	300		cm	EN 1773

FABRIC STRENGTH

Fire resistance	B1			DIN 4102
Fire resistance	M1			NF P 92 503
Fire resistance/Italy	C1			UNI 9176
Tensile strength	63	38	daN	ISO 13934-1
Tear strength	0.5	1.8	daN	ISO 13937-1
Washing stability (60°C)	<2	<2	%	ISO 5077
Dry cleaning stability	+/-2	+/-2	%	ISO 3175-2

COLOUR RESISTANCE

Colour fastness UV	5		class 8	ISO 105 B02
Colour fastness /dry friction	5		class 5	ISO 105 X12
Colour fastness /wet friction	5		class 5	ISO 105 X12
Colour fastness 60°C washing	4-5		class 5	ISO 105 C06
Colour fastness iron 100 °C	5		class 5	ISO 105 X11
Colour fastness dry cleaning	not allowed		class 5	ISO 105 D01

USE

Roll length	30 ml / 300 cm -
Recommended use	Black out curtains, hangings, interior blinds.

Consignes d'entretien



Value for this product may vary within a range of +/-5 %



Dickson Constant - 10 rue des Châteaux - BP 109 - ZI de la Pilaterie - 59443 Wasquehal France
Tél : +33 (0)3.20.45.59.59 - Fax : +33 (0)3.20.45.59.00 www.dickson-constant.com