

TECHNICAL SHEET ST GERMAIN

Updated 18-10-2012

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

OVERALL CHARACTERISTICS

Composition	100 % Polyester	Permanent Fr		
Finish	Yarn dyed			
Weave	Dobby			ISO 7211- 1
Weight	225		g/m ²	ISO 3801
Width	140		cm	EN 1773

FABRIC STRENGTH

Fire resistance	M1			NF P 92 503
Fire resistance	B1			DIN 4102
Fire resistance Europe	C1			UNE - EN 13773
Fire resistance Italy	C1			UNI 9176
Fire resistance BS	BS 5867			BS 5867-2
Fire resistance BS	BS 5852			BS 5852
Tensile strength	125	80	daN	ISO 13934-1
Tear strength	7	4.5	daN	ISO 13937-1
Stability on washing	+/- 2	+/-2	%	ISO 5077
Stability dry cleaning	+/-2	+/-2	%	ISO 3175-2
Abrasion	20 000		Nb cycles	ISO 12947-2
Pilling 5000 cycles	4-5		class 5	ISO 12945

COLOUR RESISTANCE

Colour fastness UV	4		class 8	ISO 105 B02
Colour fastness under dry friction	4		class 5	ISO 105 X12
Colour fastness under wet friction	4		class 5	ISO 105 X12
Colour fastness 40 °C washing	4		class 5	ISO 105 C06
Colour fastness iron 100 °C	4		class 5	ISO 105 X11
Colour fastness dry clean	4		class 5	ISO 105 D01

USE

Roll length	40 lm
Recommended uses	Curtains, cushions, bed-covers, interior blinds

Cleaning instructions



Values for this product may vary within a range +/- 10 %



Dickson Constant - 10 rue des Châteaux - BP 109 - ZI de la Pilaterie - 59443 Wasquehal France
Tél : +33 (0)3.20.45.59.59 - Fax : +33 (0)3.20.45.59.00 www.dickson-constant.com